

CCP-2300

Lock stitch conveyor curtain sewing machine

1.

2.

3.

watch the video

1. One needle Juki Lockstitch
2. Easily exchangeable air injected hemmer
3. Fabric clamp

- Equipped with high-speed Juki 1-needle lockstitch machine with adjustable top/bottom feed.
- Complete with two multi-functional, easily exchangeable air injected hemmers to produce perfect single and double hems up to a maximum width of 120 mm.
- Sewing unit is electrically removable to ease threading, cleaning and maintenance.
- Start/stop drawstrings placed over the full length of the frame provide an important contribution to the efficiency of the machine and the ergonomics for the operator.
- Compact, space-saving frame, equipped with a synchronised conveyor belt with a length of 550 cm.
- Simple and user-friendly operation.
- Optional: Electro hydraulic height adjustment for ergonomic work positions.
- Optional: Extended puller to process hems up to a width of 180mm.
- Optional: Exchangeable fabric guidance system.
- Optional: Tape feed system to sew pleat tapes.
- Production capacity: 50 panels per hour, bottom and side hems (average panel length of 250cm)*.
- Technical specifications:
  - Dimensions: 550 x 165 cm
  - Electric: 220 V, 1 phase, 1350 W, 16 A
  - Air: 6 bar, 3 L per cycle

** capacity strongly dependent on the operator.*

Pictures may contain options

Document	Catalogue (PDF)
Maker	Eisenkolb
Maker's pages	1 and 2
Edition	Al Borj Machinery, 2026

Eisenkolb CCP-2300

Lockstitch conveyor hemming machine

Catalogue (PDF)

Catalogue et fiche technique (PDF)

الكتالوج والمواصفات الفنية (PDF)

Product page

alborj.com/products/eisenkolb-ccp-2300

Page 1, the first page of the maker's catalogue, reproduced unchanged.

In this catalogue

1	The CCP-2300 lockstitch conveyor curtain machine
2	Features and technical specifications